

## Reinforced Branch Fittings

<b>DIMENSIONS TO</b>	<b>Dimensions :</b> from 1/8" up to 48" - MSS SP 97-12 <b>Beveled according to :</b> ASME B16.25 – 2007 <b>Threaded according to :</b> ASME B1.20.1 <b>Socket-Weld end according to :</b> ASME B16.11 – 2009 <b>Flanged as per ASME B16.5 – RF/RTJ – API 6A/6BX</b>
<b>MATERIALS</b>	<b>CARBON AND ALLOY STEEL :</b> <ul style="list-style-type: none"> <li>• A105.N – A106.B (HOT DIP GALVANISED, ELECTROPLATING)</li> <li>• A350: LF2, LF3, LF6</li> <li>• A694: F42, F52, F60, F65, F70.</li> </ul> <b>STAINLESS / AUSTENTIC STAINLES STEEL :</b> <ul style="list-style-type: none"> <li>• A182 F : 304/304L, 304H, 310, 316/316L, 316H, 316Ti, 317L, 347/347H, 321/321H, F20, F44, F904L</li> <li>• LOW ALLOY :</li> <li>• A182 : F5, F9, F11, F22, F91.</li> <li>•</li> </ul> <b>FERRITIC AUSTENTIC STAINLESS STEEL :</b> <ul style="list-style-type: none"> <li>• DUPLEX : F51 / F60; SUPER DUPLEX : F53/F55;</li> </ul> <b>NICKEL ALLOY STEEL :</b> <ul style="list-style-type: none"> <li>• INCONEL : 600 – 625 – 718.</li> <li>• INCOLLOY : 800 – 800H – 800HT – 825.</li> <li>• HASTELLOY: B2 – B3 – C22 – C276 – C2000.</li> <li>• MONEL: 200/201, 400, K500.</li> <li>• CARPENTER 20CB3 – ALLOY 20 – UNS N08020</li> </ul> <b>OTHERS :</b> <ul style="list-style-type: none"> <li>• TITANE : T40 Gr 2 – UNS R50400</li> <li>• Cu-Ni 90/10, 70/30</li> <li>• BRONZE</li> <li>• CLADDED</li> </ul>
<b>FINISHING</b>	Black, hot dip galvanizing, electro plating Stainless steel : Pickled & Passivated
<b>ENDS</b>	NPT / BSP / Socket Weld / BW / Plain End
<b>RATING</b>	2000 LBS, 3000 LBS, 6000 LBS, 9000 LBS & 10 000 LBS
<b>SCHEDULE</b>	SCH: from 5S to XXS and other heavy thicknesses